



SPECIFICATIONS

CONVEYOR LUBRICANTS

DRY FILM & FOOD GRADE LUBRICANTS

LUBRICANT	TEMP.	VISCOSITY	POUR POINT	FLASH POINT	COLOR	SUSPENDED SOLIDS
CLEAN LUBE	600°F	10°-15°F	23°F	NONE	MILKY WHITE	N/A
ULTRA-FILM 1	600°F	43°F		255°-270°F	AMBER	N/A
ULTRA-FILM 2	600°F	40°F	-30°F	145°-155°F	AMBER	N/A
ULTRA-FILM AM	250°F	-----	-30°F	142°-155°F	AMBER	N/A
LP1000	1200°F	36°F	-65°F	140°F	DARK GREY	GRAPHITE
LP1000HF	1200°F	36°F	-65°F	250°F	DARK GREY	GRAPHITE
LP750	500°F	36°F	-65°F	141°F	DARK GREY	MOS ₂
LP750HF	500°F	36°F	-65°F	250°F	DARK GREY	MOS ₂
LP505	700°F	32°F	141°F	141°F	DARK GREY	MOS ₂
LP505HF	700°F	55°F	265°F	265°F	DARK GREY	MOS ₂
GE-90-1	-----	-----	-----	-----	MILKY WHITE	-----
ULTRA-FILM FG	-----	7 CST	131°F	140°F	AMBER	N/A

All data discussed herein are believed to be correct. However, this should not be accepted or a guarantee of their accuracy, and confirming tests should be run in your own plant or laboratory. No statement should be construed as recommendation for any use which violate any patent rights. Nothing contained herein shall constitute a guarantee or warranty with respect to the products described or their use. Shelf life of most of our lubricants is 2 years. CleanLUBE and GE-90-1 have a shelf life of 1 year.