



TECHNICAL DATA SHEET

Ultra-Film AM CONVEYOR LUBRICANT

Digilube System's Ultra-Film AM Lubricant is specifically formulated and designed to lubricate various types of conveyor systems. This thin filmed anti-wear, EP lubricants is petroleum hydrocarbon based with synthetic compound mixtures. Ultra-Film AM Lubricants have no solids and perform better than other competing thin film lubricants containing solids like MOS_2 .

Ultra Film AM is formulated to effectively lubricate all types of chain conveyors which are subjected to washers and/or ambient temperatures up to 250°F. It is designed to protect against wear, rust and corrosion and can withstand sustained loads in excess of 300,000 P.S.I.

The lubricants carrier cleans and penetrates into the conveyor's wear points and evaporates, leaving behind a thin film of synthetic lubricants. Since Ultra Film AM is semi-dry, it resists drippage and reduces the attraction of airborne pollutants which can fall onto finished parts.

TYPICAL SPECIFICATIONS

| | |
|--|------------------------|
| VISCOSITY CST @ 20° C @ 68° F | 2.0 2.0 |
| POUR POINT °F / °C | -30°F / -1.1°C |
| FLASH POINT °F / °C | 142 - 155° / 61° - 68° |
| COLOR | AMBER |
| TEMPERATURE °F / °C | UP TO 250° / 121° |

All data discussed herein are believed to be correct. However, this should not be accepted or a guarantee of their accuracy, and confirming tests should be run in your own plant or laboratory. No statement should be construed as recommendation for any use which violate any patent rights. Nothing contained herein shall constitute a guarantee or warranty with respect to the products described or their use. The shelf life of this lubricant is two years.

www.digilube.com

216 East Mill St. Springboro, OH 45066 • (Office) 937-748-2209 • (Fax) 937-748-0597