



TECHNICAL DATA SHEET

LP750 CONVEYOR LUBRICANT

Digilube System's Lubricants are especially developed thin film lubricants designed to lubricate various types of conveyor systems. These anti-wear, EP lubricants are petroleum hydrocarbon based and contain MOS_2 and synthetic compound mixtures.

Our lubricants are formulated to effectively lubricate all overhead monorail conveyors which are subjected to washers and high temperature ovens. It is designed to protect against wear, rust and corrosion at elevated temperatures and can withstand repeated loads in excess of 400,000 P.S.I.

The carrier cleans and penetrates into the conveyor's wear points and evaporates, leaving behind MOS_2 and synthetic lubricants. Since they are semi-dry, they resist dripping and reduce the attraction of airborne pollutants which can fall onto finished parts.

TYPICAL SPECIFICATIONS

TEMPERATURE RANGE	up to 700°F up to 371°C
VISCOSITY	4 CST @ 40°C
POUR POINT	-21°F -30°C
FLASH POINT	147°F 63°C
COLOR	DARK GREY
SUSPENDED SOLIDS	MOS_2

LP750 has been approved in various paint shops nationwide.

All data discussed herein are believed to be correct. However, this should not be accepted as a guarantee of their accuracy, and confirming tests should be run in your own plant or laboratory. No statement should be construed as recommendation for any use which violate any patent rights. Nothing contained herein shall constitute a guarantee or warranty with respect to the products described or their use. The shelf life of this lubricant is two years.

www.digilube.com

216 East Mill St. Springboro, OH 45066 • 937-748-2209 • sales@digilube.com