



Digilube Systems, Inc. is a manufacturer of conveyor lubrication equipment, industrial maintenance lubricants and conveyor chain and rail brush cleaners. We strive to provide manufacturers, plant managers, engineers and maintenance personnel with innovative products. Our factory trained sales & field service technicians are available to provide you with a complete solution for your conveyor maintenance requirements.

## TYPES OF LUBRICANTS WE OFFER

- » Moly Free Dry Film
- » Moly Dry Film
- » Emulsions
- » Synthetics
- » Food Grade
- » Spray Lube
- » Greases



CleanLUBE by Digilube is a new generation dry film lubricant inspired by California's AQMD Rule 1144. It has:

- » No flash point
- » Virtually zero VOC's
- » Significantly improves workplace safety
- » Non-toxic, biodegradable, and low odor

## THIN FILM LUBRICANTS

Our Thin Film Lubricants are formulated to effectively clean & lubricate a wide range of Industrial applications. Digilube's Lubricants unique chemistry is designed to work with Digilube Automatic Lubrication Equipment in various types of conveyors systems. These lubricants penetrate into the wear point of chain pins & trolley bearings to protect against wear, rust and corrosion from -65° F up to 1200° F withstand repeated loads of 300,00+ PSI . Shelf life of most of our lubricants is two years, except CleanLUBE, which has a shelf life of one year.

| LUBRICANT            | TEMPERATURE RANGE           | VISCOSITY         | POUR POINT     | FLASH POINT    | COLOR       | SUSPENDED SOLIDS            |
|----------------------|-----------------------------|-------------------|----------------|----------------|-------------|-----------------------------|
| <b>CLEAN LUBE</b>    | up to 600°F<br>up to 316°C  | .66 CST @<br>40°C | 23°F<br>-5°C   | NONE           | MILKY WHITE | N/A                         |
| <b>ULTRA-FILM 1</b>  | up to 600°F<br>up to 316°C  | 4 CST @ 40°C      | 7°F<br>-14°C   | 265°F<br>130°C | AMBER       | N/A                         |
| <b>ULTRA-FILM 2</b>  | up to 600°F<br>up to 316°C  | 3 CST @ 40°C      | -30°F<br>-34°C | 147°F<br>63°C  | AMBER       | N/A                         |
| <b>ULTRA-FILM AM</b> | up to 300°F<br>up to 149°C  | 3 CST @ 40°C      | -30°F<br>-34°C | 147°F<br>63°C  | AMBER       | N/A                         |
| <b>LP1000</b>        | up to 1200°F<br>up to 649°C | 4 CST @ 40°C      | -30°F<br>-34°C | 147°F<br>63°C  | DARK GREY   | GRAPHITE / MOS <sub>2</sub> |
| <b>LP1000HF</b>      | up to 1200°F<br>up to 649°C | 5 CST @ 40°C      | 7°F<br>-14°C   | 265°F<br>130°C | DARK GREY   | GRAPHITE / MOS <sub>2</sub> |
| <b>LP750</b>         | up to 700°F<br>up to 371°C  | 4 CST @ 40°C      | -21°F<br>-30°C | 147°F<br>63°C  | DARK GREY   | MOS <sub>2</sub>            |
| <b>LP750HF</b>       | up to 700°F<br>up to 371°C  | 5 CST @ 40°C      | 7°F<br>-14°C   | 265°F<br>130°C | DARK GREY   | MOS <sub>2</sub>            |
| <b>LP505</b>         | up to 700°F<br>up to 371°C  | 4 CST @ 40°C      | -21°F<br>-30°C | 147°F<br>63°C  | DARK GREY   | MOS <sub>2</sub>            |

## FOOD GRADE LUBRICANT

|                      |                            |              |                |               |           |     |
|----------------------|----------------------------|--------------|----------------|---------------|-----------|-----|
| <b>ULTRA-FILM FG</b> | up to 500°F<br>up to 260°C | 7 CST @ 40°C | -67°F<br>-55°C | 145°F<br>63°C | COLORLESS | N/A |
|----------------------|----------------------------|--------------|----------------|---------------|-----------|-----|