



# ATS ELECTRO-LUBE

## INTERNATIONAL INCORPORATED

The **Jack-Luber** is a versatile product in the ATS line, with its proven motor-driven technology incorporating the **JACKSCREW** mechanism. It also has a replaceable, single use cartridge that changes out quickly. The **Jack-Luber** drive can run off the ATS battery pack or optional AC or DC adapters. Producing over 200 psi, the **Jack-Luber** can be used in applications with long lube lines and even through a 2-port distribution block. Tough and reliable, the **Jack-Luber** saves your time and money while giving you a trusted ATS performance.

# JACK-LUBER SERIES

## REMOTE POWER OPTIONS AVAILABLE

### SPECIFICATIONS

- Self-Contained, stand-alone automatic lubricator
- Produces over 200 psi. Single point unit can be remotely mounted up to 20ft. and up top 10ft. from distribution block
- 1/2" NPT male grease output
- UL/CUL Div. 2 Hazardous Area approved
- Remove AC/DC power options available
- Reusable motor drive unit and easily replaceable single-use cartridge
- Customer specified lube
- Customer-established dispense rates from 15 days to 2 years
- Suitable for outdoor use at (-40°F to 150°F )(-40°C to 60°C). Weatherproof cover included



### VISUAL OPERATING CONDITIONS

LED OPERATION AND WARNING INDICATORS	
1 GREEN flash every 20 sec.	Normal Operation
1 GREEN flash every sec. (approx)	Unit is dispensing grease
1 RED flash every 20 sec.	Limit switch error (unit operating in failsafe (timed dispense) mode
2 RED flashes every 20 sec.	Low battery warning
1 BLUE flash every 20 sec.	Low grease level (grease cartridge needs replacing)
2 BLUE flashes every 20 sec.	Unit paused (remote control option)
4 BLUE flashes every 20 sec.	Low temperature, dispensing is paused

**WHEN ORDERING PLEASE SPECIFY LUBRICANT.**

**NOTE:** Low Temp Lubricants must be Specified for Low Temperature applications



[www.digilube.com](http://www.digilube.com)

216 East Mill St. Springboro, OH 45066 • (Office) 937-748-2209 • (Fax) 937-748-0597