

# **ATS ELECTRO-LUBE**

#### INTERNATIONAL INCORPORATED

Powerful, motor-driven automatic lubricators, the Titan CL Luber and Titan Oiler are reliable and easily refillable. Suitable for industrial application where quality and reliability are critical. Its microprocessor controlled, energy-efficient motor delivers lubricant to a fixed-displacement pump which can product pressures over 1,00 psi. This power and reliability allow the lubricators to pump grease through long feed lines and distribution blocks that can feed several applications simultaneously. This operation is not affected by temperature or altitude. Includes an internal blender which minimizes grease separation and enhances lube consistency.

# TITAN LUBER SERIES

#### **REMOTE POWER OPTIONS AVAILABLE**

## **SPECIFICATIONS**

- Most powerful self-contained lubricator on the market
- The Titan CL and Titan CL II produces over 1,000 psi which enables it to service single-point applications up to 30' (9m) away and multi-point up to 20' (6m) away with 1/4" ID tubing
- Available with long-life replaceable battery packs or optional external power sources (AC or DC)
- Refillable using a standard grease gun
- Multiple settings to empty from 15 days to 2 years
- Remote power and remove control options available
- Suitable for indoor or outdoor use
- Dustproof and weather resistant
- Optional easy-to-install mounting plates for both single and multi-point applications available
- Operating temperature range -4°F to 131°F (-20°C to 55°C)
- LED operation and warming indicator (1-RED, 1-GREEN, 1-BLUE)
- The Titan Oiler produces up to 2,000 psi which enables it to service single-point applications up to 200ft. away and multi-point applications up to 60ft. away
- Titan Oiler has removable contaminant screen



### SIZE & DIMENSIONS

TITAN CL	12" high x 5" wide x 7.5" dia.
TITAN CL II	12" high x 5" wide x 7.5" dia.
TITAN OILER	24-1/2" high x 6" wide x 8" dia.

**NOTE:** Low Temp Lubricants must be Specified for Low Temperature applications