



LP750

by digilube systems

TECHNICAL DATASHEET

DIGILUBE'S LP750 THIN FILM LUBRICANT IS DESIGNED TO LUBRICATE VARIOUS TYPES OF CONVEYOR SYSTEMS.

TYPICAL SPECIFICATIONS

TEMPERATURE RANGE	up to 700°F up to 371°C
POUR POINT	-21°F -30°C
FLASH POINT	147°F 63°C
COLOR	DARK GRAY
SUSPENDED SOLIDS	MOS ₂
VISCOSITY	4 CST @ 40°C

FEATURES & BENEFITS

- High Temperature, Thin Film Lubricant
- Petroleum Hydrocarbon Based
- Contains MOS₂ & Synthetic Compound Mixtures
- Lubricate all Overhead Monorail Conveyors
- Anti-Wear, Extreme Pressure, and Rust / Oxidation Inhibitors
- Withstands Repeat Loads in Excess of 400,000 P.S.I
- Up To 700°F Temperature Range
- Physical Appearance - Dark Gray
- Cleans & Penetrates into the Conveyor's Wear Points & Evaporates, Leaving Behind Mos₂ and Synthetic Lubricants
- Resist Dripping and Reduce Attraction of Airborne Pollutants which can fall onto Finished Parts

*LP750 has been Approved
in Various Paint Shops
Nationwide.*

All data discussed herein are believed to be correct. However, this should not be accepted or a guarantee of their accuracy, and confirming tests should be run in your own plant or laboratory. No statement should be construed as recommendation for any use which violate any patent rights. Nothing contained herein shall constitute a guarantee or warranty with respect to the products described or their use. The shelf life of this lubricant is two years.