



TECHNICAL DATASHEET

DIGILUBE'S LP750HF THIN FILM LUBRICANT IS DESIGNED TO LUBRICATE VARIOUS TYPES OF CONVEYOR SYSTEMS.

TYPICAL SPECIFICATIONS

| | |
|--------------------------|----------------------------|
| TEMPERATURE RANGE | up to 700°F up to 371°C |
| VISCOSITY | 5 CST @ 40°C |
| POUR POINT | 7°F -14°C |
| FLASH POINT | 265°F 130°C |
| COLOR | DARK GRAY |
| SUSPENDED SOLIDS | MOS ₂ |

FEATURES & BENEFITS

- High Temperature, Thin Film Lubricant
- Petroleum Hydrocarbon based
- Contains MOS₂ & Synthetic Compound Mixtures
- Lubricate all Overhead Monorail Conveyors
- Anti-wear, Extreme Pressure, and Rust / Oxidation Inhibitors
- Withstands repeat loads in excess of 400,000 P.S.I
- Up to 700°F Temperature Range
- Physical Appearance - Dark Gray
- Cleans & Penetrates into the Conveyor's Wear Points & Evaporates, leaving behind Mos₂ and Synthetic Lubricants
- Resist Dripping and Reduce Attraction of Airborne Pollutants which can fall onto Finished Parts

LP750HF has been Approved in Various Paint Shops Nationwide.

All data discussed herein are believed to be correct. However, this should not be accepted or a guarantee of their accuracy, and confirming tests should be run in your own plant or laboratory. No statement should be construed as recommendation for any use which violate any patent rights. Nothing contained herein shall constitute a guarantee or warranty with respect to the products described or their use. The shelf life of this lubricant is two years.