TITAN SERIES

MOTOR-DRIVEN LUBRICANT DISPENSER - 1000 PSI

Powerful, motor-driven automatic lubricators, the **Titan CL Luber** and **Titan Oiler** are reliable and easily refillable. Suitable for industrial application where quality and reliability are critical. Its microprocessor controlled, energy-efficient motor delivers lubricant to a fixed-displacement pump which can product pressures over 1,00 psi. This power and reliability allow the lubricators to pump grease through long feed lines and distribution blocks that can feed several applications simultaneously. This operation is not affected by temperature or altitude. Includes an internal blender which minimizes grease separation and enhances lube consistency.



TITAN II

SPECIFICATIONS

OPTIONAL REMOTE CONTROL AVAILABLE

APPLICATION: Single and Multi-Point (up to 12 points)

SIZES: Requires 1 or 2 - 14oz Grease Cartridge - Oiler has 47oz capacity

TECHNOLOGY: Powerful mechanical fixed-displacement pump - Proven Ultimate

Series Technology

DISPENSING POWER: Over 1,000psi - Single Point can be remote mounted up to 35ft.

Multi-Point can be remote mounted up to 20ft. Oiler up to 200ft. or

Multi-Point up to 60ft using 1/4" ID hose.

Distribution Blocks available.

POWER SOURCE: Alkaline Battery Pack or remote AC/DC power

Optional Lithium Battery Pack - 8 cells

CYCLE: Refillable with Standard Grease cartridge(s)

Oiler refillable through screened port.

LUBE CHOICE: Customer replaced cartridge or refill oiler as needed

OPERATING SPAN: 15 days to 2 years. Optional custom programming available

LED INDICATORS: Tri-color LEDs to indicate normal operation, low battery, low lube

level, low temp. Oiler has low lube indicator.

WEATHERPROOF: Suitable for outdoor use in temps ranging from -40°F to 131°F

(-40°C to 55°C) Weather Cap included for cartridge & motor housing

DISPENSING RATE: Standard timed intervals or custom programming available