

# ELECTRO-LUBER SERIES



**GAS-DRIVEN LUBRICANT DISPENSER - 50PSI**



Developed in 1982, the **Electro-Luber™** uses an electro-chemical reactor cell which converts electrical energy into safe, inert gas. As the gas is produced, internal pressure fills in the sealed bellows and is applied against the orange piston. The piston then forces the lubricant out of the cylinder and onto the point of lubrication.

## SPECIFICATIONS

**REMOTE CONTROL OPTIONS AVAILABLE**

<b>APPLICATION:</b>	Single Point
<b>SIZES:</b>	Available in 2oz (60cc), 4oz (125cc), 8oz (250cc) or 16oz (475cc)
<b>TECHNOLOGY:</b>	Safe, Inert Nitrogen Gas Powered
<b>DISPENSING POWER:</b>	Up to 50 psi. Single Point can be Mounted to 3ft using 1/4" ID Hose
<b>POWER SOURCE:</b>	AA Alkaline Batteries
<b>CYCLE:</b>	Single use, Disposable
<b>LUBE CHOICE:</b>	Customer specified Lube
<b>OPERATING SPAN:</b>	15 days to 1 year on Factory Filled Unit
<b>LED INDICATORS:</b>	Red LED - Positive Verification that Unit is Working
<b>WEATHERPROOF:</b>	Waterproof (submerged) to 30ft
<b>TEMPERATURE RANGE:</b>	-40° F to 131° F / -40° C to 55° C Weather Cap available upon request
<b>DISPENSING RATE:</b>	Established constant flow rates, simply select and install

### UNITS ARE AVAILABLE WITH VARIOUS LUBE TYPES

<b>RED</b>	Standard Lube
<b>WHITE</b>	Food Grade Lube
<b>BLUE</b>	Low Temp Lube

<b>MICRO</b>	2oz - 60cc 5" high X 3-1/8" dia.
<b>MINI</b>	4oz - 125cc 5-5/8" high x 3-1/8" dia.
<b>BUDGET</b>	8oz - 250cc 6-1/8" high x 4" dia.
<b>JUMBO</b>	16oz - 475cc 6-3/4" high x 4-3/4" dia.



THE LUBERS PICTURED ABOVE ARE FILLED WITH STANDARD LUBRICANT

**You can now purchase Online,  
Scan to shop!**

