



AMERICA'S TRUSTED PROVIDER OF
CONVEYOR LUBRICATION, CLEANING
EQUIPMENT AND SERVICE.

LUBRICANT TANKS

SPECIFICATIONS

LUBRICANT TANKS	12 or 65 gallon tank - 10 Gauge
PUMP MOTOR	TEFC 1/3HP
LUBRICANT LEVEL	Electronic sensor with pvc sight gauges
PUMP	Gear 1/2 GPM factory tested 0-250 psi
FILTRATION	145 Micron
OIL VISCOSITY	Up to 25 SAE oil
POWER SOURCE	120vac, 8 amps DI-9000PS: 120vac or 24vdc
DIMENSIONS	DI-812: 22 1/2"H x 12 1/2"w x 15"l DI-865: 49"H x 22 1/2"w x 22 1/2"l
EQUIPMENT EXTERIOR	Powder coated burgundy for long-term durability

Digilube Systems offers two sizes of
Lubricant Tanks:
12 Gallon and 65 Gallon



- Each pumping station is designed to provide lubricant to both single and multiple conveyors
- 6 Gallon tank, available per request
- Tanks are available with or without a power supply (pictured with a Power Supply)
- Our DL-5003 Microprocessor can be mounted on all lubricant tanks