

TECHNICAL DATASHEET

lubricant that is best used for pinpoint lubrication. Our chain and

LP750HF.



CHAIN AND CABLE SPRAY LUBRICANT

Digilube System's lubricants are thin film lubricants designed to lubricate various types of conveyor systems. These anti-wear, EP lubricants are petroleum hydrocarbon based and contain MOS, and synthetic compound mixtures.

Our lubricants are formulated to effectively lubricate all overhead monorail conveyors which are subjected to washers and high temperature ovens. It is designed to protect against wear, rust and corrosion at elevated temperatures and can withstand repeated loads in excess of 400,000 P.S.I.

The carrier cleans and penetrates into the conveyor's wear points and evaporates, leaving behind MOS, and synthetic lubricants. Since they are semi-dry, they resist dripping and reduce the attraction of airborne pollutants which can fall onto finished parts.

SPECIFICATIONS

VISCOSITY CS @ 40°C	5 CST
POUR POINT	7°F -14°C
FLASH POINT	265°F 130°C
COLOR	DARK GRAY
TEMPERATURE RANGE	up to 700°F up to 371°C
SUSPENDED SOLIDS	MOS ₂

BENEFITS

- Stop Squeaks
- Loosens Rusty Parts
- Anti-Sling Formula Quiets Noise and Reduces Wear
- Superior Lubricant Formulated for Chains
- Dries after Entering Chain Links or Wire Cable
- Prevents Oxidation and Extends Component Life
- Contains Anti-Wear Additives, Rust Inhibitors, Moly and Graphite for Premium Performance
- **Reduces Friction**
- Frees Sticky Mechanisms >>
- Reduces Maintenance Costs
- **Prevents Rust And Corrosion**
- Longer Machinery Life

- Slides
- **Rusty Bolts**
- Pivot points
- Various Types of Chains & Cables
- Hinges
- Locks