



For the unexpected surges ordinary filters cannot handle, The AIRID Series comprised of Tsunami's product line, offers maximum protection to accommodate any application. What separates Tsunami™ from other manufacturers is that our filters are machined from 6061 aluminum and are anodized for maximum corrosion resistance, inside and out. This prevents rust and other corrosion from forming inside the filter housings unlike filters manufactured out of die cast materials. Tsunami™ filtration systems are available in up to three stage packages including water separators, oil coalescing filters and activated carbon filters.

AIR FILTRATION

COMPRISED OF TSUANMI'S PRODUCT LINE

SPECIFICATIONS

- ① **WATER SEPARATORS:** *Zero Maintenance*
Removes water up to 1 quart per minute & filters particulate down to 10 micron.
- ② **OIL COALESCING FILTERS:** *Replace Element Every 6 Months*
Oil aerosols down to .001 ppm & traps particulates down to .01 micron.
- ③ **ACTIVATED CARBON FILTERS:** *Replace Element Every 6 Months*
Removes oil vapor down to .003 ppm, removing odor & taste from the air.

8 Filter Packages Available. Each Package Includes Mounting Brackets. (See Next Page)

FILTERS ARE AVAILABLE FROM 20 SCFM TO 240 SCFM. MULTIPLE DRAINING OPTIONS AVAILABLE. MOUNTING BRACKETS SOLD SEPARATELY.

FILTER SERIES	MAXIMUM FLOW RATE	MAXIMUM PRESSURE	MAXIMUM TEMPERATURE	PORT SIZE
20 Series	20 SCFM	250 PSI	175°F	1/4" NPT
50 Series	50 SCFM	250 PSI	175°F	1/2" NPT
120 Series	120 SCFM	250 PSI	175°F	1" NPT
240 Series	240 SCFM	250 PSI	175°F	1-1/4" NPT



20 SERIES



50 SERIES



120 SERIES



240 SERIES

www.digilube.com

216 East Mill St. Springboro, OH 45066 • (Office) 937-748-2209 • (Fax) 937-748-0597



FILTRATION PACKAGES

Tsunami filtration packages come standard with float drains where water separators and oil coalescing filters are used.



PACKAGE #1

INCLUDES: WATER SEPARATOR & LUBRICATOR

TYPICAL APPLICATIONS

- AIR TOOLS
- TIRE CHANGERS
- AUTOMOTIVE LIFTS
- ROBOTICS
- MACHINE TOOL



PACKAGE #2

INCLUDES: WATER SEPARATOR, REGULATOR & LUBRICATOR

TYPICAL APPLICATIONS

- AIR TOOLS
- TIRE CHANGERS
- AUTOMOTIVE LIFTS
- ROBOTICS
- MACHINE TOOL

PACKAGE #3

INCLUDES: WATER SEPARATOR & OIL COALESCING FILTER

TYPICAL APPLICATIONS

- INDUSTRIAL PAINTING
- PLASMA CUTTING
- NITROGEN GENERATORS
- CRITICAL AUTOMATION



PACKAGE #4

INCLUDES: WATER SEPARATOR, OIL COALESCING & REGULATOR

TYPICAL APPLICATIONS

- INDUSTRIAL PAINTING
- PLASMA CUTTING
- NITROGEN GENERATORS
- CRITICAL AUTOMATION



PACKAGE #5

INCLUDES: WATER SEPARATOR, OIL COALESCING FILTER & ACTIVATED CARBON FILTER

TYPICAL APPLICATIONS

- LASER CUTTERS
- AUTOMOTIVE PAINTING
- INSPECTION ROOMS
- PRECISION EQUIPMENT
- MEDICAL
- AIR BEARINGS



PACKAGE #6

INCLUDES: WATER SEPARATOR, OIL COALESCING FILTER, ACTIVATED CARBON FILTER & REGULATOR

TYPICAL APPLICATIONS

- LASER CUTTERS
- AUTOMOTIVE PAINTING
- INSPECTION ROOMS
- PRECISION EQUIPMENT
- MEDICAL
- AIR BEARINGS



PACKAGE #7

INCLUDES: OIL COALESCING FILTER & REGULATOR

TYPICAL APPLICATIONS

- AIR TOOLS
- TIRE CHANGERS
- AUTOMOTIVE LIFTS
- ROBOTICS
- MACHINE TOOL



PACKAGE #8

INCLUDES: WATER SEPARATOR & REGULATOR

TYPICAL APPLICATIONS

- LASER
- AIR TOOLS
- TIRE CHANGERS
- AUTOMOTIVE LIFTS
- ROBOTICS
- MACHINE TOOL



www.digilube.com

216 East Mill St. Springboro, OH 45066 • (Office) 937-748-2209 • (Fax) 937-748-0597

WATER SEPARATORS

The Tsunami water separator removes water, up to 1 quart per minute, and filters particulate down to 10 micron.

DRAIN TYPE	20 SCFM	50 SCFM	120 SCFM	240 SCFM
Float Drain	J-0390	J-0131	J-0082	J-0288
Electronic Drain	-----	J-0131-ED	J-0082-ED	J-0288-ED
Pneumatic Drain	J-0390-MM	J-0131-MM	J-0082-MM	J-0850-MM

OIL COALESCING FILTERS

The Tsunami oil coalescing filter removes oil aerosols down to .001 ppm and traps particulates down to .01 micron.

DRAIN TYPE	20 SCFM	50 SCFM	120 SCFM	240 SCFM
Float Drain	J-0390-Z-FD	J-0131-Z-FD	J-0082-Z-FD	J-0289
Electronic Drain	-----	J-0131-Z-ED	J-0082-Z-ED	-----
Pneumatic Drain	J-0390-Z-MM	J-0131-Z-MM	J-0082-Z-MM	-----

ACTIVATED CARBON FILTERS

The Tsunami activated carbon filter removes oil vapor down to .003 ppm, removing odor and taste from the air.

DRAIN TYPE	20 SCFM	50 SCFM	120 SCFM	240 SCFM
Float Drain	J-0390-AC	J-0390-AC	-----	-----

