



digilube systems

TECHNICAL DATASHEET



OUR COMPLETE LINE OF ULTRA-FILM LUBRICANTS

- Lubricates various types of conveyor systems
- Thin film, anti-wear, EP lubricant
- Petroleum hydrocarbon based
- Contains synthetic compound mixtures
- Contain no solids and performs better than other competing thin film lubricants containing solids (moly / MOS_2)
- Anti-wear, extreme pressure, and rust / oxidation inhibitors
- Withstands repeat loads in excess of 300,000 P.S.I
- Cleans and penetrates into the conveyor's wear points and evaporates, leaving behind a thin film of synthetic lubricants
- Resists drippage and reduces attraction of airborne pollutants which can fall onto finished parts

TYPICAL SPECIFICATIONS

	ULTRA FILM 1	ULTRA-FILM 2	ULTRA-FILM AM	ULTRA-FILM FG
TEMPERATURE RANGE	up to 600°F (316°C)	up to 600°F (316°C)	up to 300°F (149°C)	up to 500°F (260°C)
VISCOSITY	4 CST @ 40°F	3 CST @ 40°F	3 CST @ 40°F	7 CST @ 40°F
POUR POINT	7°F (-14°C)	-30°F (-34°C)	-30°F (-34°C)	131°F (-67°C)
FLASH POINT	265°F (130°C)	147°F (63°C)	147°F (63°C)	140°F (60°C)
COLOR	AMBER	AMBER	AMBER	COLORLESS
SUSPENDED SOLIDS	N/A	N/A	N/A	N/A

All data discussed herein are believed to be correct. However, this should not be accepted as a guarantee of their accuracy, and confirming tests should be run in your own plant or laboratory. No statement should be construed as recommendation for any use which violate any patent rights. Nothing contained herein shall constitute a guarantee or warranty with respect to the products described or their use. The shelf life of these lubricants is two years.