



# CleanLUBE

by digilube systems

## TECHNICAL DATASHEET

### A NEW CONCEPT IN CONVEYOR CHAIN LUBRICATION

CleanLUBE is a premium, high-temperature, water-based lubricant that will provide unparalleled clean, cost-effective lubrication.

Features of CleanLUBE include: wear reduction, rust and corrosion protection, high temperature oxidative, thermal stability, cleaning and detergency, and low viscosity for excellent spreading and penetration.

There is nothing on the market today that compares to it.

### SPECIFICATIONS

|                             |                     |
|-----------------------------|---------------------|
| VISCOSITY CST @ 40° C       | .66                 |
| POUR POINT                  | 23°F / -5°C         |
| FLASH POINT                 | NONE                |
| COLOR                       | MILKY WHITE         |
| TEMP. RANGE                 | up to 600°F (316°C) |
| WEAR TEST (STD 4-BALL), MG* | <40                 |
| SPECIFIC GRAVITY            | .98                 |

### FEATURES & BENEFITS

- Reduced lubricant consumption
- Cleaner, longer-lasting chains
- Reduced conveyor amperage
- Contains the highest quality synthetic lubricant
- Anti-wear, extreme pressure, and rust / oxidation inhibitors
- Up to 600°F temperature range
- Physical appearance - white
- No flash point - only releases water vapor
- No graphite or moly solid build-up
- No VOC's - environmentally GREEN
- Automotive paint compatible

**\*MINUS WATER**

All data discussed herein are believed to be correct. However, this should not be accepted or a guarantee of their accuracy, and confirming tests should be run in your own plant or laboratory. No statement should be construed as recommendation for any use which violate any patent rights. Nothing contained herein shall constitute a guarantee or warranty with respect to the products described or their use. Shelf life of this CleanLUBE is 1 year.