



digilube systems

TECHNICAL DATASHEET



LP1000 LUBRICANT

- High temperature, thin film lubricant
- Petroleum hydrocarbon based
- Great for high-heat applications, such as furnace, kiln and oven chains
- Designed to protect against wear, rust and corrosion at elevated temperatures
- Contains graphite & synthetic compound mixtures
- Withstands repeat loads in excess of 100,000 P.S.I
- Cleans & penetrates into the conveyor's wear points & evaporates, leaving behind MOS_2 and synthetic lubricants
- Resist dripping and reduce attraction of airborne pollutants which can fall onto finished parts

SPECIFICATIONS

TEMPERATURE RANGE	up to 1200°F (649°C)
VISCOSITY	4 CST @ 40°C
POUR POINT	-30°F (-34°C)
FLASH POINT	147°F (63°C)
COLOR	DARK GRAY
SUSPENDED SOLIDS	GRAPHITE / MOS_2

**LUBRICATES ALL
TYPES OF CONVEYORS
SYSTEMS**

All data discussed herein are believed to be correct. However, this should not be accepted as a guarantee of their accuracy, and confirming tests should be run in your own plant or laboratory. No statement should be construed as recommendation for any use which violate any patent rights. Nothing contained herein shall constitute a guarantee or warranty with respect to the products described or their use. The shelf life of this lubricant is two years.