



# *digilube systems*

## TECHNICAL DATASHEET



# LP1000HF LUBRICANT

### SPECIFICATIONS

TEMPERATURE RANGE	up to 1200°F (649°C)
VISCOSITY	5 CST @ 40°C
POUR POINT	7°F (-14°C)
FLASH POINT	265°F (130°C)
COLOR	DARK GRAY
SUSPENDED SOLIDS	GRAPHITE / MOS <sub>2</sub>

- High temperature, thin film lubricant
- Petroleum hydrocarbon based
- Lubricate all types of conveyors
- Designed to protect against wear, rust and corrosion at elevated temperatures
- Contains graphite & synthetic compound mixtures
- Withstands repeat loads in excess of 100,000 P.S.I
- Cleans & penetrates into the conveyor's wear points & evaporates, leaving behind MOS<sub>2</sub> and synthetic lubricants
- Resist dripping and reduce attraction of airborne pollutants which can fall onto finished parts

**GREAT FOR HIGH-HEAT  
APPLICATIONS, SUCH AS  
FURNACE, KILN AND OVEN  
CHAINS**

All data discussed herein are believed to be correct. However, this should not be accepted or a guarantee of their accuracy, and confirming tests should be run in your own plant or laboratory. No statement should be construed as recommendation for any use which violate any patent rights. Nothing contained herein shall constitute a guarantee or warranty with respect to the products described or their use. The shelf life of this lubricant is two years.