



digilube systems

TECHNICAL DATASHEET

LP750 LUBRICANT

- High temperature, thin film lubricant
- Petroleum hydrocarbon based
- Contains MOS_2 & synthetic compound mixtures
- Lubricate all overhead monorail conveyors
- Anti-wear, extreme pressure, and rust / oxidation inhibitors
- Withstands repeat loads in excess of 400,000 P.S.I
- Cleans & penetrates into the conveyor's wear points & evaporates, leaving behind mos_2 and synthetic lubricants
- Resist dripping and reduce attraction of airborne pollutants which can fall onto finished parts

TYPICAL SPECIFICATIONS

TEMPERATURE RANGE	up to 700°F (371°C)
POUR POINT	-21°F (-30°C)
FLASH POINT	147°F (63°C)
COLOR	DARK GRAY
SUSPENDED SOLIDS	MOS_2
VISCOSITY	4 CST @ 40°C

**LP750 HAS BEEN
APPROVED IN
VARIOUS PAINT SHOPS
NATIONWIDE.**

All data discussed herein are believed to be correct. However, this should not be accepted or a guarantee of their accuracy, and confirming tests should be run in your own plant or laboratory. No statement should be construed as recommendation for any use which violate any patent rights. Nothing contained herein shall constitute a guarantee or warranty with respect to the products described or their use. The shelf life of this lubricant is two years.