



# *digilube systems*

## TECHNICAL DATASHEET



### ULTRA-FILM 2

Digilube's Ultra-Film 2 Lubricant is a high temperature, thin film lubricant designed to lubricate various types of conveyor systems.

Ultra-Film 2 lubricant contains no solids and performs better than other competing thin film lubricants containing solids like Moly /  $MOS_2$ . This is especially good news for companies interested in protecting the environment.

### SPECIFICATIONS

TEMPERATURE RANGE	up to 600°F (316°C)
VISCOSITY	3 CST @ 40°C
POUR POINT	-30°F (-34°C)
FLASH POINT	147°F (63°C)
COLOR	AMBER
SUSPENDED SOLIDS	N/A

All data discussed herein are believed to be correct. However, this should not be accepted or a guarantee of their accuracy, and confirming tests should be run in your own plant or laboratory. No statement should be construed as recommendation for any use which violate any patent rights. Nothing contained herein shall constitute a guarantee or warranty with respect to the products described or their use. The shelf life of this lubricant is two years.

### FEATURES & BENEFITS

- Petroleum hydrocarbon based
- Contains synthetic compound mixtures
- Anti-wear, extreme pressure, and rust / oxidation inhibitors
- Withstands repeat loads in excess of 300,000 P.S.I
- Cleans & penetrates into the conveyor's wear points & evaporates, leaving behind a thin film of synthetic lubricants
- Resists drippage and reduces attraction of airborne pollutants which can fall onto finished parts